## DUCHESNE COUNTY MONUMENT SURVEY RECORD T3S R2W SEC 16 NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (N1/16 CORNER SEC. 21) LOCATED AT LAT: 40°12'40.14273"N AND LONG: 110°06'51.09603"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER. W1/16-+ SEC 21 U.S.B.&M. N - 10N 89°24'57" W N 89°04'04" E 1-000 1323.27' 1301.68 1/4 CORNER SECTION CORNER NORTH 3/4" IRON PIN ĆORNER

## DESCRIPTION OF CORNER EVIDENCE FOUND

IN STONE MOUND

FOUND 2½" G.L.O. BRASS CAP AT THE POSITION OF THE W1/16 CORNER SET DURING THE 1922 RE—SURVEY ALONG WITH THE ORIGINAL MARKED STONE AS SHOWN HEREON.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

REFERENCED AS SHOWN.

## STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD 83 UTAH CENTRAL ZONE

> N: 7249889.154 E: 2026096.783

**LATITUDE:** 40°12′52.733″N

**LONGITUDE:** 110°07'07.948"W

PUBLIC LAND SURVEY SYSTEM GCDB ID NO. UT300030S0020W0\_320400


## CERTIFICATION

I <u>Jerry D. Allred</u>, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date 14 Nov 2011

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

SCANNED 14 Nov 2011



NO SCALE